

1. Unique identification	Each package is labelled with a unique batch number that can be traced back to the specifications drafted for this levelling mortar.	
2. Designation	Forbo Eurocol Nederland 920 Europlan Alphy; self-levelling, low-tension curing levelling mortar.	
3. Application	Levelling stone sub-floors in layers of 2 to 30 mm thick, specially designed for calcium sulphate-bound sub-floors that need to be covered with flooring.	
4. Name and contact address manufacturer	<i>Forbo Eurocol Nederland B.V.</i> <i>Industrieweg 1-2</i> <i>NL-1521 NA Wormerveer The Netherlands</i> <i>Tel. +31 75 6271600 - Fax +31 75 6283564</i> <i>Email: info.eurocol.nl@forbo.com</i>	
5. Name and contact address authorized	n/a	
6. System of assessment and verification of constancy of performance	4	
7. Activity of the notified certification body as required by the harmonized standard	n/a	
8. European Technical Assessment	n/a	
9. Declared performance	CA-C35-F10 in accordance with NEN-EN 13813:2002 Calcium sulphate-bound self-levelling levelling mortar for use inside buildings.	
<b>Essential characteristics</b>	Performance	Test method
Tensile strength after 28 days	F10	NEN-EN 13892-2:2002
Compressive strength after 28 days	C35	NEN-EN 13892-2:2002
Material behaviour in case of fire	Class F	NEN-EN 13501-1:2007+A1:2009
Released dangerous substances	see MSDS	
Declaration drafted in accordance with Annex ZA of NEN-EN 13813: 2002		
10. The performance of the points 1 and 2 are consistent with the described product specified in paragraph 9 performance. This declaration of performance is issued under the sole responsibility of the in item listed manufacturer 4.		
		Wormerveer, 24-05-2017 signed: ing. T.W. Breeuwer; Manager R&D 